



2 x 20 Backlit LCD Display



- 2 Line by 20 Character LCD Display
- Membrane Keypad with Customizable Key Legend Insert
- 24 Programmable Keys
- 1 Serial RS232/422/485 Port

System	Capacity (screens)	500
	Audio	Internal audio transducer
I/O Ports	Serial	1 x RJ45 shielded RS-232/422/485
	Power	3 pins terminal block connector, DC power input
Display	Type	STN yellow green LCD; 5 x 7 dot matrix
	Size	2 line by 20 characters
	Viewing Angle (°)	35/40/35/35 (T, B, L, R)
	Backlight	LED
Keypad	Backlight Longevity (hrs.)	50,000
	Type	Flat panel membrane
	Material	Polyester
	Lifespan	3 million operations
	Programmable Keys	24 (up to 8 screen-dependent)
Electrical	Customizable Key Legend	Yes
	Input Voltage	12 ~ 30 VDC
	Input Power	2.18 W
	Input Current	91 mA @ 24 VDC
Mechanical	Enclosure	Aluminum
	Dimensions (W x H x D)	6 x 4 x 1.77 inches [152.4 x 101.6 x 45 mm]
	Weight	0.75 lbs [0.34 kg]
	Mounting	Panel mounting
Environmental	Operating Temperature	14 ~ 149°F (-10 ~ 65°C)
	Storage Temperature	-22 ~ 176°F (-30 ~ 80°C)
	Relative Humidity	5% ~ 95% (non-condensing)
	Rating	NEMA4X / IP65
Notes	Certifications	CE / cULus (Class I, Division 2)
	Specifications subject to change without notice. For panel cutout dimensions, please refer to dimensional drawing.	

Terminals von Maple Systems liefert Ihnen



Ilse der Hütte 10, 31241 Ilse
Tel.: 05172 1290-0, Fax: 05172 1290-12
E-Mail: info@schwalenberg.com
Internet: www.schwalenberg.com